

Offers excellent flow characteristics providing the workshop with increased airflow when required and enhanced tool efficiency.

FEATURES

High flow rate - 130 cfm @ 100 psi	Hardened steel construction with corrosive resistant finish
Steel shoulder helps prevent accidental disconnection	Enhances tool efficiency
Nominal bore: 7.4 mm	Flow rate @ 6 bar (0.5 bar p.d.): 2,200 l/min
Maximum working pressure: 35 bar / 508 psi	Temperature range: -40°C to 100°C

PART NUMBER	THREAD TYPE	THREAD SIZE	INTERCHANGEABLE
AC71CM	Male	R 1/4	Cejn 320 Legris 25/26
AC71EM	Male	R 3/8	Norgren 234/238 Rectus 25/26
AC71JM	Male	R 1/2	Schrader InterCheck 35
AC71CF	Female	Rp 1/4	
AC71EF	Female	Rp 3/8	
AC71JF	Female	Rp 1/2	
AC7106	Hose Tailpiece	6 mm	
AC7108	Hose Tailpiece	8 mm	
AC7109	Hose Tailpiece	9 mm	
AC7110	Hose Tailpiece	10 mm	
AC7113	Hose Tailpiece	13 mm	

Suitable for use with: [XF Adaptors](#)



Air Tools

Air Tool Accessories

Nitrogen Inflation Equipment

Tyre Inflation Equipment

Tyre Care

Offers excellent flow characteristics providing the workshop with increased airflow when required and enhanced tool efficiency.

FEATURES

Corrosive resistant finish	Case hardened for longer life
Nominal bore: 7.4 mm	Temperature range: -40°C to 100°C
Maximum working pressure: 35 bar / 508 psi	

PART NUMBER	THREAD TYPE	THREAD SIZE	INTERCHANGEABLE
AA7101	Male	R 1/8	Cejn 320 Legris 25/26
AA7102	Male	R 1/4	Norgren 234/238 Rectus 25/26
AA7103	Male	R 3/8	Schrader InterCheck 35
AA7104	Male	R 1/2	
AA7105	Female	Rp 1/8	
AA7106	Female	Rp 1/4	
AA7107	Female	Rp 3/8	
AA7108	Female	RP 1/2	
AA7109	Hose Tailpiece	4 mm	
AA7110	Hose Tailpiece	6 mm	
AA7111	Hose Tailpiece	8 mm	
AA7114	Hose Tailpiece	9 mm	
AA7112	Hose Tailpiece	10 mm	
AA7113	Hose Tailpiece	13 mm	

Suitable for use with: [XF Couplings](#)



Workshop Accessories

Hose

Hose Fittings

Couplings & Adaptors